

FULL BRIM HELMET

NGENIE

SAFETY SERIES

PROTECTIVE SAFETY HELMET

NG022

TECHNICAL DATA SHEET

FEATURES:

- Superior top impact protection.
- Our suspension is designed to be the most comfortable in the market.
- Designed for use with **NGENIE** accessories to ensure compliance.

MARKETS

- Oil, gas, and petrochemical
- General industry and manufacturing
- Electric/utilities
- Construction
- Mining

CARE & MAINTENANCE

- Clean helmet assembly regularly with mild soap (no detergents) and warm water.
- Do not throw, drop, use as support or abuse helmet to ensure proper working condition.
- Store helmet in clean, dry environment <49°C (120°F).

SERVICE LIFE GUIDELINES

- **NGENIE FULL BRIM HELMETS** are made with high-quality, wear-resistant materials.
- Inspect the helmet before and after each use and replace any part(s) as required.
- Always replace the helmet after it has withstood an impact or penetration.
NGENIE recommends:
 - Replacing the suspension after no more than 12 months of use.
 - Replacing the shell after no more than five (5) years of use.
- Please consult user instructions for additional details.



SPECIFICATIONS

STANDARDS COMPLIANCE	ANSI/ISEA Z89.1-2014
CLASSIFICATION	Type I, Class E
CERTIFICATION	Third-party
APPLICATION(S)	General Purpose
PRODUCT SIZES	Standard (6½" to 8")
SHELL MATERIAL	Virgin high-density polyethylene (HDPE) with UV inhibitor
AVAILABLE STYLES	Full Brim
AVAILABLE SUSPENSIONS	Ratchet Suspension
REQUIREMENTS FOR OPTIONAL FEATURES (Z89.1)	Reverse Donning, Lower Temperature, Higher Temperature
COLORS	White, Red, Blue, Green, Yellow, and Orange
OTHER PPE	NGENIE accessories, hat-mounted hearing protectors, face protection system, and chinstraps
PRODUCT DIMENSIONS	30.8 x 26.7 x 15.2 cm 0.44 kg
SHIPPING CARTON DIMENSIONS (BOX OF 10)	53 x 33 x 44 cm 7.2 kg

TECHNICAL ASSISTANCE/ADDITIONAL INFO

For more information about **NGENIE** products, please contact us at info@n-genie.com or visit n-genie.com